

## Specifications

Model	450	550
Cutting width	11'	13.6'
Transportation width (approx.)	92"	96"
Transportation height / length (approx.)	74" / 186"	87" / 189"
Recommended horsepower	45 hp	55 hp
Wing flex*	40° up 10° down	40° up 10° down
Deck overlap	6"	6"
Gear box rating at 540 RPM	120 hp divider box, 30 hp wing boxes	
Hitch type	Cast clevis (standard)	
Driveline main / wings	Series 4-80° CV / series 2	Series 4-80° CV / series 2
Deck width / thickness	4' / 10 Ga.	5' / 7 Ga.
Deck tires	8 (15" x 6" x 6")	10 (15" x 6" x 6")
Main frame tire	2 (27" x 10-1/2" x 15")	2 (27" x 10-1/2" x 15")
Blades per deck / overlap	3 blades / 1-5/8"	3 blades / 2-5/8"
Blade tip speed	15,485 ft/min	15,829 ft/min
Cutting height	1-1/2" to 4-1/2"	1-1/2" to 4-1/2"
Mower drive system	2 belt B groove	2 belt B groove
Front roller	4" x 7" UHMW Poly	4" x 7" UHMW Poly
Weight	3380 lbs	3880 lbs

\* Not recommended for operation greater than 30°, actual measurement based on mower deck flex.

Model	650	750
Cutting width	16'	19.9'
Transportation width (approx.)	102"	108"
Transportation height / length, (approx.)	105" / 206"	123" / 211"
Recommended horsepower	65 hp	80 hp
Wing flex*	40° up 10° down	40° up 10° down
Deck overlap	6"	6"
Gear box rating at 540 RPM	120 hp divider box, 30 hp wing boxes	
Hitch type	Cast clevis (standard)	
Driveline main / wings	Series 4-80° CV / series 2	Series 4-80° CV / series 2
Deck width / thickness	6' / 7 Ga.	7' / 7 Ga.
Deck tires	10 (15" x 6" x 6")	12 (15" x 6" x 6")
Main frame tire	2 (27" x 10-1/2" x 15")	2 (27" x 10-1/2" x 15")
Blades per deck / overlap	3 blades / 2-5/8"	3 blades / 2-5/8"
Blade tip speed	18,737 ft/min	18,552 ft/min
Cutting height	1-1/2" to 4-1/2"	1-1/2" to 4-1/2"
Mower drive system	2 belt B groove	2 belt B groove
Front roller	4" x 7" UHMW Poly	4" x 7" UHMW Poly
Weight	4270 lbs	4530 lbs

\* Not recommended for operation greater than 30°, actual measurement based on mower deck flex.