



DRAG SCRAPERS



RDS SERIES DRAG SCRAPERS are heavy-duty and designed for a variety of applications such as general earth moving, road repairs, leveling ditches, building terraces, filling low spots and spreading topsoil. Available in 8', 10', and 12' sizes from 2 1/2 to 3 3/4 cubic yard capacities. Equipped with two 15" wheels less tires, 1/2" x 6" reversible cutting edge, 3/8" x 30" high x 40" long side plates and removable 4" x 4" swivel tongue. Features 12" clearance when raised. Equipped with a manual tilt feature. Requires one or two 3" x 8" double acting hydraulic cylinder and hoses and two G70 x 15" tires.

Model	DS SERIES
WORKING WIDTHS	8', 10', 12'
MOLD BOARD HEIGHT & THICKNESS	1/4" x 24"
SIDE PLATES	3/8" x 30" x 40"
TONGUE	4" x 4" x 3/8" bolt on
APPROXIMATE WEIGHT	1450 (8'), 1650 (10'), 1860 (12')
APPROXIMATE HP RANGE	75 to 175
TIRES	Less tires, required (2) G70 x 15 tires
HYDRAULICS	*Requires (1 or 2) 3" x 8" dbl. acting cylinder & hoses
TILT	Standard
CAPACITY	2-1/2 cu.yd. (8'), 3-1/8 cu.yd. (10'), 3-3/4 cu.yd. (12')
MOLDBOARD CUTTING EDGE	1/2" x 6" reversible

Specifications subject to change without notice

Innovative, Rugged & Labor Saving Attachments