




## RCR812 HAY RUNNER

- HIGH CAPACITY DESIGN
- 8, 10 & 12 WHEEL MODELS
- INDEPENDENT RAKE ARMS
- 55" & 60" RAKE WHEELS
- HIGH CLEARANCE FRAME
- RAKE COMES IN RED OR GREEN
- FRONT WHEEL LOCK UP ON 10- AND 12-WHEEL MODELS
- GREASEABLE WHEEL HUBS
- NARROW TRANSPORT WIDTH
- EASY RAKE ANGLE ADJUSTMENT w/TURNBUCKLE
- HEAVY DUTY DESIGN
- SINGLE SIDE RAKING
- 15" TIRES
- PATENTED ADJUSTABLE TORSION SPRINGS
- 3" x 12" CYLINDERS
- OPTIONAL TANDEM AXLES
- OPTIONAL CENTER WHEEL KIT
- CENTER WHEEL KIT HAS INDEPENDENT FLOATING 55" WHEELS
- REAR TWO WHEELS PIVOT TO ADJUST WINDROW



# RCR812 HAY RUNNER SPECIFICATIONS



**MADE IN USA**

DISTRIBUTED BY

MANUFACTURED BY

**Ogden Metalworks, Inc.**

PO Box 128 • 301 N. Marilyn Ave.  
Ogden, IL 61859

PH: (217) 582-2552 • Fax: (217) 582-2746

[www.ogdenmetalworks.com](http://www.ogdenmetalworks.com)

Email:

[ogdenmetalworks@ogdenmetalworks.com](mailto:ogdenmetalworks@ogdenmetalworks.com)

Rear-Hinging	RCR8		RCR10		RCR12	
RAKING WIDTH*	MIN	MAX	MIN	MAX	MIN	MAX
	17'	20 ½'	19'	22 ½'	21'	26 ½'
NUMBER OF WHEELS	8		10		12	
WEIGHT	1960 LBS.		2135 LBS.		2300 LBS.	
	MIN			MAX		
TRANSPORT WIDTH**	8'			10 ½'		
TRANSPORT LENGTH**	17'			21'		
TRANSPORT HEIGHT**	9'			11'		
WINDROW WIDTH**	3'			6'		
WHEEL HUBS & BEARINGS	GREASABLE TAPERED ROLLER BEARINGS					
WHEEL DIAMETER	55" & 60"					
TIRE DIAMETER	7MM & 7.5MM					
NUMBER OF TINES PER WHEEL	40					
RAKE WHEEL SUSPENSION	INDEPENDENT ARM FOR EACH WHEEL – TEFLON BUSHINGS AT PIVOT					
GROUND PRESSURE ADJUSTMENT	PATENTED ADJUSTABLE TORSION SPRING ON EACH WHEEL					
HYDRAULIC CYLINDERS	3" x 12" DOUBLE ACTING					
HYDRAULIC PRESSURE REQUIREMENT	MINIMUM 1900 PSI					
HYDRAULIC REMOTES REQUIRED	1 SET					
TIRES	205/75-15"					
HYDRAULIC CENTER WHEEL KIT	OPTIONAL					
WALKING TANDEM AXLES	OPTIONAL					
WIND GUARDS	OPTIONAL					

Specifications subject to change

- \* Will vary depending on crop conditions
- \*\* Dimensions vary per model

## RCR812 HAY RUNNER

