





Ref. 10.DL.1000/1000-C





Boom Mower













• Hydraulic boom mower, perfect for road maintenance and other applications. For use with hydrostatic machines.

• Ease of visibility during operation for operators comfort

 Electro Hydraulic control valves for smooth and precise operation (proportional controls also available as an option). Hydraulic flow regulator for control of speed for boom movements

• Hydraulic safety system to protect boom from damage.

• Auto-Self leveling system on first section of boom

• Optional pruning heads, sign cleaning brushes, root puller/cutters, floating mower couplers, etc. can easily be interchanged

	/	and the second se	E C	
-			G	F
A				E
		в	<u> </u>	



Dimensions	10DL1000	10DL1000-C
A (Maximum Horizontal Height)	63 in.	54 in.
В	174 in.	135 in.
С	178 in.	39 in.
D	63 in.	42 in.
E	37 in.	37 in.
F	215 in.	174 in.
G	34 in.	40 in.

All data subject to change without previous notice.



OFFICE 6535 NW 84th Ave. Miami, Florida, 33167 Tel. +1-786-542-6122 info@coneac.com www.coneac.com



Factory Pol. Ind. La Pobla, nave 19-21 08260 Súria (BCN) SPAIN Tel. +34 93 869 40 50 - Fax +34 93 868 25 77 euroimplementos@euroimplementos.com www.euroimplementos.com

