









## Concrete Mixer

Ref. 08.BM



The 08.BM is an attachment that optimizes the utilization of the carrier, allowing you to mix concrete, wherever and whenever, it is needed in three simple steps: load, mix, unload.

The 08.BM is highly recommended for the construction and repair of streets, sidewalks sewers, curbs, and gutters.

The 08.BM can be coupled to mini-loaders, excavators, wheel loaders, backhoes, and/or telehandlers.

As an option, a hydraulically opened grill is available.

Technical Specifications								
08.BM.	0150	0200	0250	0350	0450	0600	0700	1100
Width (in)	49.6	49.6	58.3	62.2	64.2	74.8	74.8	84.6
Capacity (yd <sup>3</sup> )	0.20	0.26	0.33	0.46	0.59	0.78	0.92	1.44
Drive *	G	G	С	С	С	С	С	С
Weight (lbs)	595	595	838	875	1000	1389	1565	2756
Maximum Flow (gpm)	10.5	10.5	15.9	19.8	19.8	19.8	39.6	30.4
Maximum Pressure (psi)	2465	2465	2538	2900	2900	2900	2973	2973
* G = Gear Reduction C = Hidraulic via Chain								

All specifications and technical data subject to change without prior notice.



OFFICE 6535 NW 84th Ave. Miami, Florida, 33167 Tel. +1-786-542-6122 info@coneac.com www.coneac.com



**Factory** Pol. Ind. La Pobla, nave 19-21 08260 Súria (BCN) SPAIN Tel. +34 93 869 40 50 - Fax +34 93 868 25 77 euroimplementos@euroimplementos.com www.euroimplementos.com

