



Backhoe for tractor



All data and images subject to change without prior notice

Backhoe for tractor, with vertical stabilizers, side shift with mechanical blocking, hydraulic oil tank integrated into the frame, outside operation seat, coupling for 3 point hitch

Optional equipment

- ✓ Gearbox and gear pump
- ✓ Side shift with hydraulic blocking
- ✓ Hydraulic installation hammer
- ✓ Quick coupler

Ref.	Digging depth mm	Standard bucket mm	HP required
OP00 A	2000mm/78"	300mm/12"	25-50
OP02 A	2500mm/98"	300mm/12"	50-70
OP03 A	2850/112"	400/16"	50-90
OP3.2 A	3100/122"	400/16"	70-100
OP04 A	3400/134"	400/16"	+100

TECNICAL DATA	OP 03	OP 03
A.DIGGING DEPTH	2850 mm	112"
B.MAXIMUM HEIGHT	3340 mm	131"
C.HORIZONTAL REACH	3340 mm	131"
D.UNLOADING HEIGHT	2170 mm	85"
E.GROUND CLEARANCE	380 mm	15"
F.CARRIAGE WIDHT*	1500/1700 mm	59/67"
G.TOTAL WIDHT WITH STABILIZERS*	1570/1770 mm	62/70"
H.LATERAL DISPLACEMENT*	860 mm	34"
I.HEIGHT RETAKEN	2250 mm	88"
J.STABILIZER RUN	500 mm	19"
SWING ARC	180°	180°
BUCKET ROTATION	206°	206°
WEIGHT WITHOUT BUCKET	650 Kg	650 Kg
MAXIMUM LIFT CAPACITY	1000 Kp	1000 Kp
SWING,BOOMS AND BUCKET CONTROLS	2 HAND LEVERS	2 HAND LEVERS
STABILIZERS CONTROLS	2 HAND LEVERS	2 HAND LEVERS
AUXILIARY HYDR.CONTROLS	1 HAND LEVER	1 HAND LEVER
LATERAL DISPLACEMENT HYDR.BLOCKED	OPTIONAL	OPTIONAL
HYDR.CIRCUIT FOR ATTACHMENTS	OPTIONAL	OPTIONAL
VALVES PROTECTING AUX. HYDR.CIRCUIT	YES	YES
VALVES PROTECTING HYDR.CIRCUIT	YES	YES
PRESSURE MEASURING VALVES	YES	YES
DEJECTABLE CONTROL VALVES	YES	YES
OUT SEAT	OPTIONAL	OPTIONAL
QUICK ATTACHMENT SYSTEM	OPTIONAL	OPTIONAL

BUCKETS	OP 03
200 mm /8"	YES
250 mm / 10"	YES
300 mm /12"	YES
350 mm / 14"	YES
400 mm / 16"	YES
450 mm / 18"	YES
500 mm / 20"	YES
600 mm / 24"	YES
800 mm (cleaning) / 31"	YES
1000 mm (cleaning) / 40"	YES